



DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY  
AFFAIRS (PERA)  
BOARD AND CODE ADMINISTRATION DIVISION

## NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/pera/](http://www.miamidade.gov/pera/)

**DAB Door Company, Inc.**  
12195 NW 98<sup>th</sup> Avenue  
Hialeah Gardens, FL 33018

**SCOPE:** This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

**DESCRIPTION:** 18'-2" Wide x 16' High (Reinforced) Steel Sectional Garage Door w/ Window Lite Option

**APPROVAL DOCUMENT:** Drawing No. 99-24, titled "Sectional Garage Door", dated 09/22/1999, with last revision G dated 10/13/2011, sheets 1 through 5 of 5, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P.E., bearing the Miami-Dade County Product Control revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

**MISSILE IMPACT RATING:** Large and Small Missile Impact Resistant

**LABELING:** A permanent label with the manufacturer's name or logo, manufacturing address, model number, the positive and negative design pressure rating, indicate impact rated if applicable, installation instruction drawing reference number, approval number (NOA), the applicable test standards, and the statement reading 'Miami-Dade County Product Control Approved' is to be located on the door's side track, bottom angle, or inner surface of a panel.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA # 09-0324.07 and consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Carlos M. Utrera, P.E.



*[Signature]*  
02/23/2012

NOA No. 12-0110:12  
Expiration Date: March 10, 2013  
Approval Date: March 1, 2012  
Page 1

**NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED**

**A. DRAWINGS**

1. Drawing No. **99-24**, titled "Sectional Garage Door", dated 09/22/1999, with last revision G dated 10/13/2011, sheets 1 through 5 of 5, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P.E.

**B. TESTS "Submitted under NOA # 09-0324.07"**

1. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94  
2) Large Missile Impact Test per FBC, TAS 201-94  
3) Cyclic Wind Pressure Loading per FBC, TAS 203-94  
4) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94  
along with marked-up drawings and installation diagram of a DAB 824 24 GA Sectional Residential Garage Door, prepared by Hurricane Engineering & Testing, Inc, Test Reports No. **HETI-08-2133A and B**, dated 06/10/2008, signed and sealed by Candido F. Font, P.E.


2. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94  
2) Large Missile Impact Test per FBC, TAS 201-94  
3) Cyclic Wind Pressure Loading per FBC, TAS 203-94  
4) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94  
along with marked-up drawings and installation diagram of a DAB 824 24 GA Sectional Garage Door, prepared by Hurricane Engineering & Testing, Inc, Test Reports No. **HETI-08-2149A/B**, dated 06/27/2008, signed and sealed by Candido F. Font, P.E.

**"Submitted under NOA # 08-1106.05"**

3. Test report on Tensile Test per ASTM E 8 of the above sectional garage door's skin, prepared by Hurricane Engineering & Testing, Inc, Test Report No. **HETI-08-T139/A**, dated 06/27/2008, signed and sealed by Candido F. Font, P.E.
4. Test report on Salt Spray (Corrosion) Test per ASTM B 117 of a painted G-40 steel panels, prepared by Celotex Corporation, Test Report No. **258592**, dated 08/17/1998, signed by W. A. Jackson, P.E. **"Submitted under NOA # 03-0210.04"**

**C. CALCULATIONS "Submitted under NOA # 09-0324.07"**

1. Anchor verification calculations and structural analysis prepared by Al-Farooq Corporation, complying with F.B.C 2004/2007, dated 01/20/2009, signed and sealed by Humayoun Farooq, P.E.
2. Anchor verification calculations and structural analysis prepared by Al-Farooq Corporation, complying with F.B.C 2004/2007, dated 08/25/2008, signed and sealed by Humayoun Farooq, P.E. **"Submitted under NOA # 08-1106.05"**

  
02/23/2012

Carlos M. Utrera, P.E.  
Product Control Examiner  
NOA No. 12-0110.12

Expiration Date: March 10, 2013  
Approval Date: March 1, 2012

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

**D. QUALITY ASSURANCE**

1. Miami-Dade Department of Permitting, Environment, and Regulatory Affairs (PERA)

**E. MATERIAL CERTIFICATIONS**

1. Notice of Acceptance No. **08-0305.02**, issued to SABIC Innovative Plastics, for their Lexan Sheet Products, approved on 04/24/2008 and expiring on 07/17/2013.
2. Notice of Acceptance No. **07-1016.07**, issued to Insulfoam, LLC, for their Insulfoam Expanded Polystyrene Insulation, approved on 11/29/2007 and expiring on 11/29/2012.
3. Notice of Acceptance No. **11-0926.07**, issued to Dyplast Products, LLC, for their Expanded Polystyrene Block Type Insulation, approved on 11/10/2011 and expiring on 01/11/2017.
4. Notice of Acceptance No. **11-0926.06**, issued to Dyplast Products, LLC, for their Dyplast ISO-C1 Polyisocyanurate Insulation, approved on 11/10/2011 and expiring on 01/11/2017.

*"Submitted under NOA # 05-0228.02"*


5. Test Report on Accelerated Weathering Using Xenon Arc Light Apparatus Test per ASTM G155 of "PVC Extrusion Material", prepared by Hurricane Engineering & Testing, Inc., Report No. **HETI 04-A002**, dated 09/27/2004, signed and sealed by Rafael E. Droz-Seda, P.E.
6. Test Reports on Tensile Test per ASTM D638 of "PVC Extrusion Material", prepared by Hurricane Engineering & Testing Inc., Report No. **HETI 04-T251**, dated 11/29/2004 signed and sealed by I. Ghia, P.E.
7. Test Report on Self-Ignition Temperature Test, Rate of Burn Test and Smoke Density Test of "REHAU non-foam PVC extrusion material", prepared by ETC Laboratories, Report No. **04-761-15019.0**, dated 05/06/2004, signed and sealed by J. L. Doldan, P.E.

**F. STATEMENTS**

1. Statement letter of code conformance to 2010 FBC and no financial interest, issued by Al-Farooq Corporation, dated 10/26/2011, signed and sealed by Javad Ahmad, P.E.

*"Submitted under NOA # 09-0324.07"*

2. Laboratory code compliance statements issued by Hurricane Engineering & Testing, Inc, for Test Reports No. **HETI-08-2149A/B B** and **HETI-08-T139/A**, dated 06/10/2008 and 06/27/2008, all signed and sealed by Candido F. Font, P.E.

  
02/23/2012

Carlos M. Utrera, P.E.

Product Control Examiner

NOA No. 12-0110.12

Expiration Date: March 10, 2013

Approval Date: March 1, 2012

7-1/2" X 3" X .120" GALV. STEEL  
END ROLLER HINGES  
WITH OPTIONAL DELRON SLEEVE

7-1/2" X 2-1/4" X .071"  
GALV. STEEL CENTER HINGE  
WITH OPTIONAL DELRON SLEEVE  
W/ (4) #14 X 5/8" SMS

#14 X 1/2" SMS  
4 PER HINGE

2/ LOCK  
DOOR

3/4" W X 3/16" THK.  
LATCH

SPRING LOADED SLIDE BOLT LOCK (BOTH SIDES)  
FASTENED W/ (4) #14 X 1/2" S.M.S.  
5/8" MIN. LOCK ENGAGEMENT CONFORMS TO  
FBC 1012 REGARDING GARAGE DOORS

8-1/4" X 4-1/2" X 1-1/2"  
STEEL PLATE .0115" THK.  
WITH (8) #14 X 5/8" SMS

.128 DIA. GALV. AIRCRAFT TYPE  
CABLE & NICO-PRESS SLEEVE  
W/ MIN. 5 TO 1 SAFETY FACTOR


SCHEDULE 'A'

DOOR WIDTHS	# OF CENTER STILES
9'-1" TO 11'-10"	4
12'-0" TO 13'-10"	5
14'-0" TO 15'-10"	6
15'-11" TO 18'-2"	7

DOOR HEIGHT	CONSISTS OF	
6'-6"	2 SECTIONS 18"	2 SECTIONS 21"
6'-9"	1 SECTION 18"	3 SECTIONS 21"
7'	4 SECTIONS 21"	-
7'-3"	-	-
7'-6"	5 SECTIONS 18"	-
7'-9"	4 SECTIONS 18"	1 SECTION 21"
8'	3 SECTIONS 18"	2 SECTIONS 21"
8'-3"	2 SECTIONS 18"	3 SECTIONS 21"
8'-6"	1 SECTION 18"	4 SECTIONS 21"
8'-9"	5 SECTIONS 21"	-
9'	6 SECTIONS 18"	-
9'-3"	5 SECTIONS 18"	1 SECTION 21"
9'-6"	4 SECTIONS 18"	2 SECTIONS 21"
9'-9"	3 SECTIONS 18"	3 SECTIONS 21"
10'	2 SECTIONS 18"	4 SECTIONS 21"
10'-3"	1 SECTION 18"	5 SECTIONS 21"
10'-6"	6 SECTIONS 21"	-
10'-9"	6 SECTIONS 18"	1 SECTION 21"
11'	5 SECTIONS 18"	2 SECTIONS 21"
11'-3"	4 SECTIONS 18"	3 SECTIONS 21"
11'-6"	3 SECTIONS 18"	4 SECTIONS 21"
11'-9"	2 SECTIONS 18"	5 SECTIONS 21"
12'	1 SECTIONS 18"	6 SECTIONS 21"
12'-3"	7 SECTIONS 21"	-
12'-6"	6 SECTIONS 18"	2 SECTIONS 21"
12'-9"	5 SECTIONS 18"	3 SECTIONS 21"
13'	4 SECTIONS 18"	4 SECTIONS 21"
13'-3"	3 SECTIONS 18"	5 SECTIONS 21"
13'-6"	2 SECTIONS 18"	6 SECTIONS 21"
13'-9"	1 SECTION 18"	7 SECTIONS 21"
14'	8 SECTIONS 21"	-
14'-3"	6 SECTIONS 18"	3 SECTIONS 21"
14'-6"	5 SECTIONS 18"	4 SECTIONS 21"
14'-9"	4 SECTIONS 18"	5 SECTIONS 21"
15'	3 SECTIONS 18"	6 SECTIONS 21"
15'-3"	2 SECTIONS 18"	7 SECTIONS 21"
15'-6"	1 SECTION 18"	8 SECTIONS 21"
15'-9"	9 SECTIONS 21"	-
16'	6 SECTIONS 18"	4 SECTIONS 21"

BOTTOM BRACKET  
FOR 3" TRACK

BOTTOM BRACKET  
FOR 2" TRACK



OUTSIDE KEYPED LOCK  
LOCK BAR LOCKING SHOWN  
ALTERNATE TO LOCKS SHOWN ABOVE

TOP FIXTURE 5-1/2" X 2-3/4" X 0.1"  
STEEL PLATE WITH ONE 5/16-18 MS W/ NUT  
FASTENED TO END STILE WITH  
(6) #14 X 3/4" SELF DRILLING SCREWS

CENTER STILES  
SEE SCH. 'A'

OPTIONAL DOOR VIEWER  
TO BE INSTALLED AT  
ANY CENTER STILE

OPTIONAL VENT  
(3) 5" WIDE AT 7" O.C. MAX.  
OPENING AREA NOT TO EXCEED  
120 SQ. IN.

COLONIAL DESIGN

OPTIONAL FLUSH FACE  
WOOD GRAIN DESIGN

MAX. DOOR WIDTH  
18'-2"

INSIDE ELEVATION  
RAISED PANEL EMBOSSED DOOR

THIS PRODUCT IS RATED FOR LARGE MISSILE IMPACT

### GENERAL NOTES

- THIS PRODUCT HAS BEEN DESIGNED AND TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE 2010 EDITION INCLUDING HIGH VELOCITY HURRICANE ZONE.
- ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS. ANCHOR EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.
- ALL BOLTS, NUTS AND WASHERS SHALL BE ZINC PLATED CARBON STEEL.
- ANCHORING OR LOADING CONDITIONS OTHER THAN THOSE SHOWN IN THESE DETAILS ARE NOT PART OF THIS APPROVAL.
- A LOAD DURATION INCREASE IS USED IN DESIGN OF ANCHORS INTO WOOD ONLY.

Engr: JAVAD AHMAD  
CIVIL  
FLA. PE # 70592  
C.A.N. 3538

DESIGN PRESSURE RATING = + 55.0 PSF  
- 64.0 PSF

DAB DOOR MODEL 824  
MAX. SIZE 18'-2" WIDE X 16'-0" HIGH

PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No 12-0110-12  
Expiration Date 03/10/2013  
By *[Signature]*  
Miami Dade Product Control

**AL-FAROOQ CORPORATION**  
ENGINEERS & PRODUCT DEVELOPMENT  
1235 S.W. 87 AVE  
MIAMI, FLORIDA 33174  
TEL. (305) 264-8100 FAX. (305) 262-6978  
GARAGE/99-24DAB


### SECTIONAL GARAGE DOOR

**DAB DOORS INC.**  
12195 N.W. 98 TH. AVE.  
HIALEAH GARDENS, FL. 33018  
TEL. (305) 556 - 6624


revisions:	no.	date	by	description
	C	8.11.05	H	UPDATED FOR 2004 FBC
	D	02.28.06		REV. PER BCCO COMMENTS
	E	03.28.06		GENERAL REVISION
	F	01.23.09		GENERAL REVISION
	G	10.13.11		UPDATED TO 2010 FBC

date: 09-22-99  
scale: 1/2"=1'-0"  
dr. by: HAMID  
chk. by:


drawing no.  
**99-24**  
sheet 1 of 5





1ST SECTION (BOTTOM)  
REINFORCING



INTERMEDIATE SECTIONS  
REINFORCING




TOP SECTION  
REINFORCING



SOLID BRASS DOOR VIEWER

BY 'SCHLAGE SECURITY HARDWARE'  
INSTALLED IN 9/16\"/>

FOR CONNECTION OF WOOD BUCK  
TO MASONRY SEE NOTE ON SHEET 4



SECTION B-B

Engr: JAWAD, AHMAD  
CIVIL  
FLA. PE. # 70592  
C.A.N. 3538

PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No 12-0110,12  
Expiration Date 03/10/2013  
By *[Signature]*  
Miami Dade Product Control


**afC**  
**AL-FAROOQ CORPORATION**  
ENGINEERS & PRODUCT DEVELOPMENT  
1235 S.W. 87 AVE  
MIAMI, FLORIDA 33174  
TEL. (305) 264-8100 FAX. (305) 262-6978  
GARAGE\99-24DAB

SECTIONAL GARAGE DOOR  
**DAB DOORS INC.**  
12195 N.W. 98 TH. AVE.  
HIALEAH GARDENS, FL. 33018  
TEL (305) 556 - 6624


revisions:	no	date	by	description
C	8.11.05	H	ANCHORS	REV.
D	02.28.06	REV.	PER BCCO	COMMENTS
E	03.28.08	GENERAL	REVISION	
F	01.23.09	NO CHANGE		
G	10.13.11	NO CHANGE		

date: 09-22-99  
scale: -  
dr. by: HAMID  
chk. by:



drawing no.  
**99-24**  
sheet 2 of 5



SECTION A-A  
SEE SHEET 2 FOR LOCATION OF REINFORCING TRUSSES



TRACK CONFIGURATION



AVAILABLE TRACK OPTIONS

Engr: JAVAD AHMAD  
CIVIL  
FLA. PE # 70592  
C.A.N. 3533

NOV 07 2011

PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No 12-0119-12  
Expiration Date 03/10/2013

By *[Signature]*  
Miami Door Product Control

**AL-FAROOQ CORPORATION**  
ENGINEERS & PRODUCT DEVELOPMENT  
1235 S.W. 87 AVE  
MIAMI, FLORIDA 33174  
TEL (305) 264-8100 FAX (305) 262-6978

**a f c**

GARAGE 99-24DAB

---

SECTIONAL GARAGE DOOR


**DAB DOORS INC.**  
12195 N.W. 98 TH. AVE.  
HIALEAH GARDENS, FL. 33018  
TEL (305) 556 - 6624

no	date	by	description
C	8.11.05	H	ANCHOR SPACING REV.
D	02.28.06		REV. PER BCCO COMMENTS
E	03.28.08		GENERAL REVISION
F	01.23.09		GENERAL REVISION
G	10.13.11		NO CHANGE THIS SHEET

---

date: 09-22-99  
scale: -  
dr. by: HAMID  
chk. by:

drawing no.  
**99-24**  
sheet 3 of 5



STEEL STRUCTURE BY OTHERS  
MUST SUPPORT THE LOADS IMPOSED  
BY DOOR SYSTEM

5/16" DIA. BOLTS  
WITH WASHER & NUT  
AT 12" O.C. MAX.

1-1/4" X 2-1/2" X 14 GA  
CONT. STEEL ANGLE

12 GA. GALV. STEEL  
FLAT BRACKETS ±3" LONG  
AT 6" O.C. IN DOOR OPNG.  
AT 18" O.C. ABOVE DOOR OPNG.  
CONNECTED TO CONT. ANGLE  
W/ (3) SPOT WELDS AT EACH SIDE

EDGE DIST.

1-1/2"

2-1/8" X 1" X 14 GA.  
GALV. STEEL TRACK  
FASTENED TO TRACK PLATES  
W/ (2) 1/4-20X5/8" TRUSS HD.  
SLOTTED M.S. & LOCK NUT

ANCHOR SPACING				
ANCHORS	STRUCTURE	EMBED	SPACING	EDGE DIST.
3/8" HLC SLEEVE BY 'HILTI'	CONC.	1-1/4"	6"	2-1/2"
1/2" HLC SLEEVE BY 'HILTI'	FILLED BLOCK	1-1/2"	8"	4"
3/8" DYNABOLT BY 'ITW'	CONC.	1-1/2"	6"	3-3/4"
1/2" DYNABOLT BY 'ITW'	FILLED BLOCK	1-7/8"	6"	4"
3/8" POWER-BOLT BY 'POWERS'	CONC.	2"	6"	2-1/2"
3/8" SLEEVE-ALL BY 'SIMPSON'S'	CONC.	1-1/2"	6"	3"

CONCRETE  $f'_c$  = 3000 PSI MIN.  
C-90 GROUT FILLED BLOCK  $f'_m$  = 2000 PSI MIN.

#### ALTERNATE TRACK INSTALLATION

#### WOOD FRAME BUILDINGS

STUD WALLS OR DOOR OPENING (NOT BY DAB DOORS)  
SHALL BE FRAMED SOLID BY NOT LESS THAN  
(3) 2X6 PRESSURE TREATED GRADE 2 SYP OR BETTER  
WOOD STUDS.

STUD WALLS TO BE CONT. FROM FOOTING TO TIE BEAM.  
ENGINEER OF RECORD TO VERIFY ADEQUACY OF THE  
SUPPORTING STRUCTURE.

#### WOOD BUCK CONNECTION TO MASONRY

TRACK SHALL BE SECURED WITH CONT. STEEL ANGLE TO PRESSURE  
TREATED 2X6 SYP WOOD JAMBS WHICH SHALL BE ANCHORED TO  
GROUTED REINFORCED MASONRY BLOCK WALL OR CONC. COLUMN WITH

1/4" ULTRACON BY 'ELCO' WITH SPACING OF  
7" O.C. INTO BLOCK WALL, WITH 2-1/4" MIN. EMBED  
7" O.C. INTO 3000 PSI CONCRETE, WITH 1-3/4" MIN. EMBED  
2-1/2" MIN. EDGE DISTANCE


1/4" TAPPER BY 'POWERS' WITH SPACING OF  
4" O.C. INTO BLOCK WALL, WITH 1-1/2" MIN. EMBED  
5" O.C. INTO 3000 PSI CONCRETE, WITH 1-3/4" MIN. EMBED  
3" MIN. EDGE DISTANCE

3/8" CONFLX BY 'ELCO' OR  
3/8" LDT BY 'ITW' WITH SPACING OF  
11" O.C. INTO 3000 PSI CONCRETE, WITH 2-1/2" MIN. EMBED  
3" MIN. EDGE DISTANCE

3/8" HLC SLEEVE BY 'HILTI' WITH SPACING OF  
7" O.C. INTO 3000 PSI CONCRETE, WITH 1-1/4" MIN. EMBED AND  
2-1/2" MIN. EDGE DISTANCE

THE BLOCK WALL CELLS SHALL BE GROUT FILLED AND REINFORCED  
WITH FOUR # 5 BARS EXTENDING INTO FOOTING AND INTO TIE BEAMS  
ALL BARS SHALL BE CONTINUOUS FROM TIE BEAMS TO FOOTING.

#### PREPARATION OF JAMBS BY OTHERS



Engr. JAVAD AHMAD  
CML  
FLA. PE. # 70592  
C.A.N. 3538

NOV 07 2011

**PRODUCT REVISED**  
as complying with the Florida  
Building Code  
Acceptance No 12-0110.12  
Expiration Date 02/10/2013

By *[Signature]*  
Miami Trade Product Control

#### SECTIONAL GARAGE DOOR

**DAB DOORS INC.**  
12195 N.W. 98 TH. AVE.  
HIALEAH GARDENS, FL. 33018  
TEL (305) 556 - 6624



revisions:	no	date	by	description
	C	18.11.05	H	ANCHOR SPACING REV.
	D	02.28.06		REV. PER BCCO COMMENTS
	E	03.28.08		GENERAL REVISION
	F	01.23.09		GENERAL REVISION
	G	10.13.11		NO CHANGE THIS SHEET

date: 09-22-99  
scale: -  
dr. by: HAMID  
chk. by:

drawing no.  
**99-24**  
sheet 4 of 5




**AL-FAROOQ CORPORATION**  
ENGINEERS & PRODUCT DEVELOPMENT  
1235 S.W. 87 AVE  
MIAMI, FLORIDA 33174  
TEL (305) 264-8100 FAX (305) 262-6978  
GARAGE 99-24DAB

\* PLASTIC COMPLIES WITH  
SECTION 2612 OF FBC 2007  
SEE EVIDENCE PAGE




**a f c**

**AL-FAROOQ CORPORATION**  
ENGINEERS & PRODUCT DEVELOPMENT  
1235 S.W. 87 AVE  
MIAMI, FLORIDA 33174  
TEL. (305) 264-8100 FAX. (305) 262-6978  
GARAGE 99-24DAB



INSIDE ELEVATION  
RAISED PANEL EMBOSSED DOOR WITH OPTIONAL WINDOWS



Engr: JAVAD AHMAD  
CIVIL  
FLA. PE # 70592  
C.A.N. 3538  
NOV 07 2011

PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No 12-0114-12  
Expiration Date 03/10/2013  
By *[Signature]*  
Miami Trade Product Control

SECTIONAL GARAGE DOOR  
**DAB DOORS INC.**  
12195 N.W. 98 TH. AVE.  
HIALEAH GARDENS, FL. 33018  
TEL. (305) 556 - 6624

revisions:		no	date	by	description
		E	03.28.08		GENERAL REVISION
		F	01.23.09		GENERAL REVISION
		G	10.13.11		NO CHANGE THIS SHEET

date: 09-22-99  
scale: -  
dr. by: HAMID  
chk. by:  
drawing no.  
**99-24**  
sheet 5 of 5